

SPOT65-R

MAGNETIC TRACK SERIES




SPECIFICATIONS

Model No.	SP65-R
Power Consumption(±10%)	8W
Input Voltage	24VDC
Driver Type	Constant Current (CC)
Dimming	Yes
Luminous Flux (±10%)	481W
Efficacy(4000K Ra70)	31lm/W
Correlated Color Temperature	2700K, 3000K, 3500K, 4000K, 5000K
Color Rendering Index	Ra80 (Ra90 optional)
Beam Angle	10°, 20°, 30°
UGR level	NA
Mounting Option	Track Mounted
Material	Aluminum Alloy Body, Polycarbonate Optical Lens
Finish	Powder Coating
Fixture Color	Black/White
IP Rating	IP20
Operating Temperature	-30°C to + 50°C(-22°F to 122°F)
Life Time of LED @Ta=25°C	50000 Hours
Warranty	5 Years
Application	Residential, Retail, Office, etc.

DISTRIBUTION


3000K 90Ra

10°




h(m)	E(lx)	Φ(m)
1	4109	Φ0.20
2	1027	Φ0.40
3	456	Φ0.61
4	256	Φ0.81
5	164	Φ1.02

20°



h(m)	E(lx)	Φ(m)
1	2805	Φ0.27
2	701	Φ0.55
3	311	Φ0.82
4	175	Φ1.10
5	112	Φ1.37

30°




h(m)	E(lx)	Φ(m)
1	645	Φ0.58
2	161	Φ1.16
3	71	Φ1.74
4	40	Φ2.32
5	25	Φ2.91


■ Sandy Black □ Sandy White ■ Golden




TRACK ADAPTERS



SENIOR



CURVY



JUNIOR





ORDERING INFORMATION

EXAMPLE: PR-MT-SP65R-S-B-3000-80-T-30

SERIES	TRACK	FIXTURE COLOR	CCT(K°)	CRI	DIMMING	BEAM ANGLE
PR-MT-SP65R	S: Senior	B: Black	2700	80	D: Dali	10°
	J: Junior	W: White	3000	90	T: Triac	20°
	R: Curvy		3500		V: 0-10V	30°
			4000		O: None	
			5000			