

PENDANT ZOEY

MAGNETIC TRACK SERIES



■ Sandy Black □ Sandy White

PROMAX




SPECIFICATIONS

Model No.	Pendant Zoey
Power Consumption(±10%)	10W
Input Voltage	24VDC
Driver Type	Constant Current (CC)
Dimming	Yes
Luminous Flux (±10%)	498 lm
Efficacy(4000K Ra70)	50 lm/W
Correlated Color Temperature	2700K, 3000K, 3500K, 4000K, 5000K
Color Rendering Index	Ra80 (Ra90 optional)
Beam Angle	Diffuse
Mounting Option	Track Mounted
Material	Aluminum Alloy Body, Polycarbonate Optical Lens
Finish	Powder Coating
Fixture Color	Black/White
IP Rating	IP20
Operating Temperature	-30°C to + 50°C(-22°F to 122°F)
Life Time of LED @Ta=25°C	50000 Hours
Warranty	5 Years
Application	Residential, Retail, Office, etc.

DISTRIBUTION


3000K 90Ra

Diffuse




h(m)	E(lx)	Φ(m)
1	298	Φ1.63
2	75	Φ3.27
3	33	Φ4.90
4	19	Φ6.54
5	12	Φ8.18


DIMENSIONS



SENIOR



CURVY



JUNIOR

ORDERING INFORMATION

EXAMPLE: PR-MT-PTZ-S-B-3000-80-T-D

SERIES	TRACK	FIXTURE COLOR	CCT(K°)	CRI	DIMMING	BEAM ANGLE
PR-MT-PTZ	S: Senior	B: Black	2700	80	D: Dali	D: Diffuse
	J: Junior	W: White	3000	90	T: Triac	
	R: Curvy		3500		V: 0-10V	
			4000		O: None	
			5000			

PREMIER

3740 William St, Burnaby, BC V5C 3H7

Phone: +1 (604) 294-2334, Toll free: +1 (877) 294-2334, Fax: +1 (604) 294-2126

www.premierlight.ca

Magnetic Track -Pendant Zoey

Last update: Mar. 2024

Page 1 of 1