

PENDANT50-R

MAGNETIC TRACK SERIES






Sandy Black
 Sandy White
 Golden
 Black bronze

SPECIFICATIONS


Model No.	Pendant50R
Power Consumption(±10%)	10W
Input Voltage	24VDC
Driver Type	Constant Current (CC)
Dimming	Yes
Luminous Flux (±10%)	682 lm
Efficacy(4000K Ra70)	68 lm/W
Correlated Color Temperature	2700K, 3000K, 3500K, 4000K, 5000K
Color Rendering Index	Ra80 (Ra90 optional)
Beam Angle	18°, 24°, 36°
Mounting Option	Track Mounted
Material	Aluminum Alloy Body, Polycarbonate Optical Lens
Finish	Powder Coating
Fixture Color	Black/White/Gold/Bronze
IP Rating	IP20
Operating Temperature	-30°C to + 50°C(-22°F to 122°F)
Life Time of LED @Ta=25°C	50000 Hours
Warranty	5 Years
Application	Residential, Retail, Office, etc.

DISTRIBUTION


3000K 90Ra




DIMENSIONS



SENIOR



CURVY



JUNIOR



3740 William St, Burnaby, BC V5C 3H7
 Phone: +1 (604) 294-2334, Toll free: +1 (877) 294-2334, Fax: +1 (604) 294-2126
 www.premierlight.ca

Magnetic Track -Pendant50-R
 Last update: Mar. 2024
 Page 1 of 2

PENDANT50-R

MAGNETIC TRACK SERIES



ORDERING INFORMATION

EXAMPLE: PR-MT-PT50R-S-B-3000-80-T-30

SERIES	TRACK	FIXTURE COLOR	CCT(K°)	CRI	DIMMING	BEAM ANGLE
PR-MT-PT50R	S: Senior	B: Black	2700	80	D: Dali	18°
	J: Junior	W: White	3000	90	T: Triac	24°
	R: Curvy	G: Gold	3500		V: 0-10V	36°
		Z: Bronze	4000		O: None	
			5000			



3740 William St, Burnaby, BC V5C 3H7

Phone: +1 (604) 294-2334, Toll free: +1 (877) 294-2334, Fax: +1 (604) 294-2126

www.premierlight.ca

Magnetic Track -Pendant50-R

Last update: Mar. 2024

Page 2 of 2