

# DF05

## DECORATIVE WALL MOUNTED SPECIFICATIONS



Job Information	
Project Name	
Type	
Location	
Quantity	
Date	

## DESCRIPTION

This lighting fixture is constructed using durable, recyclable felt, offering an eco-friendly solution that aligns with modern performance needs. Its sound-absorbing design helps minimize background noise, promoting better acoustic conditions in any environment. The flame-resistant nature of the felt also enhances safety, making it suitable for use in residential, commercial, and hospitality settings alike. Engineered for ease of use, the fixture includes a remote control for simple and efficient lighting adjustments. It's also easy to maintain, compatible with standard vacuuming, typical household cleaning products, or even a basic mixture of salt and water. With its robust construction, sleek design, and functional benefits, this lighting option fits naturally into a wide range of interior spaces.

## OVERVIEW

- Quality - Powered by CREE high efficiency COB LED chip
- Felt material for acoustic properties
- Customizable felt finish colors for fixture's reflector and body
- Compatibility – Optional flicker-free TRIAC/120V or 1-10V/100-277V true color - 90+ CRI, produces outstanding illumination

## PERFORMANCE

MODEL NAME	DF05
POWER CONSUMPTION(±10%)	3W
INPUT VOLTAGE	120 VAC
DIMMING	TRIAC/0-10V
CCT	3000
CRI	90
FELT DIMENSIONS	L x W x H 300 x 220 x 50 (11.8" x 8.6" x 1.9") 340 x 320 x 50 (13.3"x12.5"x 1.9")
MOUNTING OPTIONS	WALL/SURFACE MOUNTED
FINISH	ACOUSTIC FELT
FINISH COLOR	COFFEE, DARK GREY, OLIVE, BLACK, GREY, DARK GREY, ORANGE
IP RATING	IP20
OPERATING TEMPERATURE	-30°C TO + 50°C(-22°F TO 122°F)
LIFE TIME OF LED @TA=25°C	50000 HRS LM80 ANSI/IES
WARRANTY	3 YEARS
APPLICATIONS	INDOORS

# DF05

## DECORATIVE WALL MOUNTED SPECIFICATIONS

### PRODUCT ORDERING GUIDE

EXAMPLE: DF05-3W-1-120-3000-90-N-OR

SERIES	WATTAGE	SIZE	VOLTAGE	CCT	CRI	DIMMING	FELT COLOR
DF05	3 W	1: 300 x 220 x 50 (11.8" x 8.6"x 1.9" ) 2: 340 x 320 x 50 (13.3"x12.5"x 1.9")	120: 120 VAC	2700	90	T: TRIAC	C: COFFEE
				3000		V: 0-10V	OL: OLIVE
				4000		N: NONE	DG: DARK GREY B: BLACK G: GREY OR: ORANGE N: NAVY BLUE

