

GN01 (CG60051, CG60052)

GOOSENECK ACCENT LIGHT SPECIFICATIONS



Job Information	
Project Name	
Type	
Location	
Quantity	
Date	

DESCRIPTION

Exterior-rated downlight fixture with rigid curved arm and spun or formed metal shade. Constructed from corrosion-resistant materials with weather-sealed electrical components for long-term outdoor operation. Provides controlled, directional illumination for façades, signage, entries, and perimeter lighting applications. Available with E26/E27 lamp holder or integrated LED light engine. Offered in multiple arm projections, shade diameters, and durable powder-coat finish options. Listed for wet locations; compatible with dimming options depending on lamping selection.

OVERVIEW

- Four different arms to choose from
- 19W/26W LED or E26/E27 base, bulbs can be ordered separately. Maximum wattage allowed in 150W.
- Listed for outdoor applications, corrosion resistant
- Custom colors can be ordered

PERFORMANCE

MODEL NAME	GN01-CG60051	GN01-CG60052
SHADE DIAMETER	9.5"	12"
LAMPING	19W/26W/E26/E27 MAX 150W	
INPUT VOLTAGE	120-277/347V	
DIMMING	TRIAC/0-10V	
MATERIAL	SPUN ALUMINUM, CLEAR ACRYLIC LENS	
FINISH	BLACK/WHITE/GREY/BRONZE/CUSTOM	
IP RATING	IP65	
OPERATING TEMPERATURE	-20°C TO + 55°C (-4°F TO 131°F)	
LIFESPAN OF LED @TA=25°C	50000 HRS	
WARRANTY	5 YEARS	

PRODUCT ORDERING GUIDE

EXAMPLE: GN01-CG60051-E26-3000-A2-BK-V-S

SERIES	WATTAGE(W)	CCT	DIMMING	ARM TYPE	FINISH
GN01-CG60051	19W	2700	N: ON/OFF	A1	BK: BLACK
GN01-CG60052	26W	3000	T: TRIAC	A2	DG: DARK GREY
	E26 (MAX 150W)	4000	V: 0-10V	A3	WH: WHITE
	E27 (MAX 150W)	5700		A4	CUSTOM COLOR (SPECIFY)

GN01 (CG60051, CG60052)

GOOSENECK ACCENT LIGHT SPECIFICATIONS

DIMENSIONS (inch)

