

GN02

GOOSENECK ACCENT LIGHT SPECIFICATIONS



Job Information	
Project Name	
Type	
Location	
Quantity	
Date	

DESCRIPTION

Exterior-rated downlight fixture with rigid curved arm and spun or formed metal shade. Constructed from corrosion-resistant materials with weather-sealed electrical components for long-term outdoor operation. Provides controlled, directional illumination for façades, signage, entries, and perimeter lighting applications. Available with power adjustable integrated LED light engine. Offered in multiple arm projections, shade diameters, and durable powder-coat finish options. Listed for wet locations; compatible with dimming options.

OVERVIEW

- Wattage Adjustable: 100%-80%-60%
- CCT Adjustable: 3000K-4000K-5000K
- Inner On/Off Photocell
- Different arms and shades options
- Tool-less arm & shade change
- 270° Vertical rotation
- 0-10V Dimming
- Bronze, black, white or other customized finish

PERFORMANCE

MODEL NAME	GN02
SHADE DIAMETER	9 3/4" DOME OR 11" STRAIGHT
POWER CONSUMPTION	25W ADJUSTABLE
INPUT VOLTAGE	120-277VAC
EFFICACY	130 LM/W
CCT	CCT TUNABLE (3K/4K/5K)
CONTROL	PHOTOCELL, 0-10V DIMMING
MATERIAL	ALUMINUM
FINISH	BLACK/WHITE/GREY/BRONZE/CUSTOM
IP RATING	IP65
OPERATING TEMPERATURE	-20°C TO + 55°C(-4°F TO 131°F)
LIFESPAN OF LED @TA=25°C	50000 HRS
WARRANTY	5 YEARS

PRODUCT ORDERING GUIDE

EXAMPLE: GN02-N-A2-BK

SERIES	SHADE TYPE	DIMMING	ARM TYPE	FINISH
GN02	D: DOME S: STRAIGHT	V: 0-10V N: ON/OFF	A1 A2 A3	BK: BLACK BZ: BRONZE WH: WHITE CUSTOM COLOR (SPECIFY)

DIFFERENT ARM TYPES



A1



A2



A3

Tool-free assembly



DIFFERENT SHADE TYPES



Straight



Dome

GN02

GOOSENECK ACCENT LIGHT SPECIFICATIONS

DIMENSIONS (inch)

